



Your Dreams, Our Challenge

IPC-4101E Slash Sheet Reference Guide

IPC Slash Sheet	Part Number	DK (nominal)	Description
IPC-4101E/29	N4000-13, N4000-13SI N4103-13 (Laminate) N4203-13 (Prepreg)	3.60, 3.20	High Speed, Low Loss, Modified Epoxy Flame Rating: 94 V-0 * Microwave Performance, Modified Epoxy Flame Rating: 94 V-0
	N4000-13EP, N4000-13EPSI N4103-13EP (Laminate) N4203-13EP (Prepreg)	3.60, 3.20	
	N4350-13RF *, N4380-13RF * N4^^-13RF (Laminate) * N4^^-13RF (Prepreg) *	3.50, 3.80	
IPC-4101E/30	N5000 N5105## (Rigid Laminate ≥ 0.020) N5205## (Thin Laminate < 0.020) N5305## (Prepreg)	3.60	BT Epoxy Flame Rating: 94 V-0
IPC-4101E/40 IPC-4101E/41 IPC-4101E/42	N7000-2HT N7105-2 HT (Rigid Laminate ≥ 0.020) N7205-2 HT (Thin Laminate < 0.020)	3.50	Non-MDA Toughened Polyimide Flame Rating: 94 V-0 * Non-MDA Toughened Polyimide Flame Rating: 94 V-1 † Non-MDA Toughened and Filled Polyimide Flame Rating: 94 V-1
	N7000-3 * N7105-3 (Rigid Laminate ≥ 0.020) * N7205-3 (Thin Laminate < 0.020) * N7305-3 (Prepreg) *	3.50	
	N7000-3F † N7105-3F (Rigid Laminate ≥ 0.020) † N7205-3F (Thin Laminate < 0.020) † N7305-3F (Prepreg) †	4.00	
IPC-4101E/71	N8000 N8105## (Rigid Laminate ≥ 0.020) * N8205## (Thin Laminate < 0.020) * N8305## (Prepreg) *	3.50	Cyanate Ester Flame Rating: 94 V-0
IPC-4101E/98	N4000-29, N4000-29NF N4105-29 (Laminate) N4205-29 (Prepreg)	4.30	High Tg Multifunctional Epoxy Flame Rating: 94 V-0
IPC-4101E/99	N4000-29 N4105-29 (Laminate) N4205-29 (Prepreg)	4.30	Lead Free, High Tg Multifunctional Epoxy Flame Rating: 94 V-0

IPC Slash Sheet	Part Number	DK (nominal)	Description
IPC-4101E/102	Meteorwave 1000, 1000NF Meteorwave 1000 L (Laminate) Meteorwave 1000 P (Prepreg)	3.40	Very to Extreme Low Loss, Very High Reliability PPE Flame Rating: 94 V-0 * Ultra to Extreme Low Loss, Very High Reliability PPE, Controlled 3.5 Dk Flame Rating: 94 V-0
	Meteorwave 2000 Meteorwave 2000 L (Laminate) Meteorwave 2000 P (Prepreg)	3.20	
	Meteorwave 3000, 3350 * Meteorwave 3000 L (Laminate) Meteorwave 3000 P (Prepreg)	3.60, 3.50	
	Meteorwave 4000, M-Ply Meteorwave 4000 L (Laminate) Meteorwave 4000 P (Prepreg)	3.40, 3.38	
	Meteorwave 8000, 8350 * Meteorwave 8000 L (Laminate) Meteorwave 8000 P (Prepreg)	3.28, 3.50	
	Meteorwave 8300 Meteorwave 8000 L (Laminate) Meteorwave 8000 P (Prepreg)	3.00	
	Meteorwave M1 Meteorwave M1 (Laminate) Meteorwave M1P (Prepreg)	3.1	
IPC-4101E/126 IPC-4101E/129	N4000-29 N4105-29 (Laminate) N4205-29 (Prepreg)	4.30	Lead Free, High Tg Multifunctional Epoxy Flame Rating: 94 V-0

IPC-4103B Slash Sheet Reference Guide

IPC Slash Sheet	Part Number	DK (nominal)	Description
IPC-4103B/200	TLP-5 TLY-5 TLY-5A TLY-5Z	2.20 2.20 2.17 2.2	PTFE/Woven Glass
IPC-4103B/210	TLY-3	2.33	PTFE/Woven Glass
IPC-4103B/220	602 TLT TLX	2.45 - 2.80 2.45 - 2.65 2.40 - 2.65	PTFE/Woven Glass
IPC-4103B/230	603 RF-30* TLC TLE TSM-DS3*, DS3b*, DS3M* NF-30* Meteorwave 8300 [†] Meteorwave 8000 L (Laminate) [†]	2.75 - 3.00 3.00 2.75 - 3.00 2.94 - 2.95 2.94 - 3.00 3.00 3.00	PTFE/Woven Glass *PTFE/Ceramic Woven Glass [†] Ultra Low Loss, Very High Reliability PPE Flame Rating: 94 V-0
IPC-4103B/240	RF-35*, 35A2*, 35HTC*, 35TC* TLC-32 TLC-35 TLF-35A* Meteorwave M1 ^{**} Meteorwave M1 (Laminate) Meteorwave M1P (Prepreg) Meteorwave 3350 ^{††} Meteorwave 3000 L (Laminate) ^{††} Meteorwave 3000 P (Prepreg) ^{††} Meteorwave 8350 ^{††} Meteorwave 8000 L (Laminate) ^{††} Meteorwave 8000 P (Prepreg) ^{††}	3.50 3.20 3.50 3.50 3.10 3.50 3.50	PTFE/Woven Glass *PTFE/Ceramic Woven Glass ^{**} Very to Extreme Low Loss, Very High Reliability PPE Flame Rating: 94 V-0 ^{††} Ultra to Extreme Low Loss, Very High Reliability PPE, Controlled 3.5 Dk Flame Rating: 94 V-0
IPC-4103B/250	TRF-41 TRF-43 TRF-45	4.10 4.30 4.50	PTFE/Ceramic Woven Glass
IPC-4103B/270	RF-60A RF-60TC	6.15 6.15	PTFE/Ceramic Woven Glass
IPC-4103B/280	RF-10	10.20	PTFE/Ceramic Woven Glass

IPC Slash Sheet	Part Number	DK (nominal)	Description
IPC-4103B/520	fastRise FR-25 fastRise FR-26, FR-27	2.45 2.64	PTFE/Ceramic/Adhesive
IPC-4103B/530	TPG-30 [†] fastRise FR-27, FR-28 fastRise FR-EZpure Meteorwave 8300 * Meteorwave 8000 P (Prepreg) *	3.00 2.74 2.80 3.00	[†] PTFE/Ceramic BT Woven Glass Prepreg PTFE/Ceramic/Adhesive Hydrocarbon/Silica/Non-Reinforced * Ultra Low Loss, Very High Reliability PPE Flame Rating: 94 V-0
IPC-4103B/540	TPG-32 TPG-35	3.20 3.50	PTFE/Ceramic BT Woven Glass Prepreg
IPC-4103B/560	fastRise FR-TC	4.80	Hydrocarbon/Alumina/Non-Reinforced

IPC-4203B Slash Sheet Reference Guide

IPC Slash Sheet Number	Part Number	DK (nominal)	Description
IPC-4203B/26	fastRise FR-EZ-22p fastRise FR-EZ-33p	2.44 2.51	PTFE/Ceramic/Adhesive

